

Silo-Diagramm

Diagramme de Silo

	Fixit 160	Fixit 166	Fixit 180 evo	Fixit 508 Fixit 516	Fixit 508 P	Fixit 583 Fixit 585	Fixit 920 Fixit 950
Schüttdichte t/m ³ Masse volumique t/m ³	0.95	0.92	1.33	1.75	1.75	1.65	1.55
Konus (c)	2.10	2.10	3.00	4.00	4.00	3.70	3.50
c +1.0 m	5.70	5.50	8.00	10.50	10.50	9.90	9.50
c +2.0 m	9.30	9.00	13.00	17.10	17.10	16.10	15.20
c +3.0 m	12.90	12.50	18.00	23.70	23.70	22.40	21.00
c +4.0 m	16.40	15.90	23.00	30.30	30.30	28.60	28.60
c +4.3 m	17.50	17.00	24.50	32.30	32.30	30.40	29.60
Stromanschluss Raccordement électrique	32 Amp. 5 Pol	32 Amp. 5 Pol	32 Amp. 5 Pol	32 Amp. 5 Pol	32 Amp. 5 Pol	32 Amp. 5 Pol	32 Amp. 5 Pol
Wasserdruck bei Betrieb Pression d'eau nécessaire				5 bar	5 bar	5 bar	5 bar
mind. Wassermenge Fonctionnement et débit minimum					1500 l/h		

	Fixit 606	Fixit 610	Fixit 622	Fixit 820 (evo) Fixit 830 (evo)
Schüttdichte t/m ³ Masse volumique t/m ³	1.15	1.45	1.10	1.40
Konus (c)	2.60	3.30	2.50	3.20
c +1.0 m	6.90	8.70	6.60	8.50
c +2.0 m	11.20	14.20	10.50	13.70
c +3.0 m	15.60	19.60	14.90	19.00
c +4.0 m	19.90	25.10	19.00	24.30
c +4.3 m	21.20	26.70	20.20	32.00
Stromanschluss Raccordement électrique	32 Amp. 5 Pol	32 Amp. 5 Pol	32 Amp. 5 Pol	32 Amp. 5 Pol
Wasserdruck bei Betrieb Pression d'eau nécessaire	5 bar	5 bar	5 bar	5 bar
mind. Wassermenge Fonctionnement et débit minimum				2500 l/h

