



STRUCTURAL MINERAL PAINT 071

Mineral paint in the garage system

Areas of application: Paint intended for spray application to execute a finishing layer in the TURBO - WG garage system
Creates a dashed texture

Properties:

- Water resistant after curing.
- Frost-proof
- Vapor-permeable
- High grip
- Environmentally friendly

Application procedure:



| Technical data | |
|-----------------------------|--------------------------------|
| Item no. | 315184 |
| Packaging type | |
| Quantity per unit | 25 kg |
| Unit per pallet | 48 Pcs/pallet |
| Colour | White |
| Density | approx. 1.2 g/cm ³ |
| Granulation | 0 - 1 mm |
| Consumption | approx. 2.15 kg/m ² |
| Drying time | from 12 to 48 hours |
| Hardening time | approx. 24 h |
| Soluble chromium VI content | ≤ 0.0002 % (2ppm) |
| Reaction to fire | A1 |

The product conforms to: • ICiMB-KOT-2017/0002

Material base:

- Hydrated lime
- Texturing aggregate
- Mineral fillers
- White Portland cement

Surface: The mineral wool insulation bonded to the garage ceiling must be covered with TYNKOLIT-U 340 at least 24 hours before starting the finishing work.

Types of substrate: **Lamella wool:** Zagruntować TYNKOLITEM-U 340
Pre-primed lamella wool: Zagruntować TYNKOLITEM-U 340

Preparation: Pour the dry mix maintaining the proportion of 6.5l of water per 25kg of dry mix. Pour gradually to a water container, mixing with a low-speed mixer to produce a homogeneous, lump-free mass. Leave to mature for 5 minutes and mix thoroughly again.
To avoid color differences, prepare each consecutive batch in the same manner, using an identical amount of water.

Application procedure: Apply the prepared paint using a spray application unit with suitable structure and precisely selected nozzle (4-8mm)
While performing works and during drying process, protect from frost, rainfalls, too high temperatures and strong winds.

Application conditions: Apply in temperatures from +5 °C to +25 °C, these temperature refer to air, groundwork and product temperature.
Use a dedicated spray application unit with a precisely selected nozzle



STRUCTURAL MINERAL PAINT 071

Mineral paint in the garage system

| | |
|-----------------------------|---|
| Instructions: | Use the entire set of products in the thermal insulation system. Apply the paint in an even layer, maintaining uniform structure on the entire surface |
| Storage: | Maximally 12 months In dry areas and in non-damaged packaging |
| General information: | This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing. |
