Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier

Trade name:

MAX PROTECT 042

Polysilicone BIO-Render.

Relevant identified uses of the substance or mixture and uses advised against

Life cycle stages
C/PW Consumer use / Widespread use by professional workers

Sector of Use
SU19 Building and construction work

Product category
PC9a Coatings and paints, thinners, paint removers

Process category
PROC11 Non industrial spraying
PROC19 Manual activities involving hand contact

Environmental release category
ERC10a / ERC11a Widespread use of articles with low release

Article category
AC0 Other

Application of the substance / the preparation
Structural skim - Product for an industrial, technical and private use for coating building surfaces.
For all other uses is advised against/ not recommended.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KREISEL - Technika Budowlana Sp. z o.o.
ul. Szarych Szeregów 23
60-462 Poznań
Poland

Tel. +48 61 846 79 00
Fax +48 61 846 79 09
sekretariat@kreisel.pl
www.kreisel.pl

Further information obtainable from:
Bartosz Polaczyk - Tel.: +48 510 022 908, +48 61 84 67 966, bartosz.polaczyk@kreisel.pl
On working days 8 a.m. - 4 p.m.

Emergency telephone number



National poisons information centre: +44/(0)171 - 635 9191
National Health Service: 111
European emergency call: 112

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 1)

SECTION 2: Hazards identification

Classification of the substance or mixture
The product is not classified, according to the Globally Harmonised System (GHS).

Label elements
GHS label elements Void

Hazard pictograms
Void

Signal word
Void

Hazard statements
Void

Additional information:
EUH208 Contains 2-Methyl-2H-isothiazol-3-one, 2-Octyl-2H-isothiazol-3-one, 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Other hazards
No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

Chemical characterization: Substances
This product is a mixture.

Mixtures

Description:
Mixture of acrylat dispersion and fillers with nonhazardous additions.

Dangerous components:		
CAS: 13463-67-7 EINECS: 236-675-5 Index number:... 022-006-00-2 REACH: 01-2119489379-17	Titanium dioxide (<1% particles ≤ 10µm, Note 10)	1 - 2.5%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 2)

CAS: 2682-20-4 EINECS: 220-239-6 REACH: 01-2120764690-50	2-Methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 1, H410 (M=1); Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.0015 %	< 0.0015%
CAS: 26530-20-1 EINECS: 247-761-7 Index number:... 613-112-00-5 REACH: 01-2120768921-45	2-Octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD_{50} oral: 125 mg/kg LD_{50} dermal: 311 mg/kg Specific concentration limit: Skin Sens.1A; H317: C ≥ 0.0015 %	≥ 0.00025 - < 0.0015%
CAS: 64359-81-5 EINECS: 264-843-8 Index number:... 613-335-00-8 REACH: [2]	4,5-dichloro-2-octyl-2H-isothiazol-3-one Acute Tox. 2, H330; Skin Corr. 1C, H314; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 ATE: LD_{50} oral: 567 mg/kg Specific concentration limits: Skin Irrit. 2;H315: C ≥ 0.025 % Eye Irrit. 2; H319: C ≥ 0.025 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥ 0.00025 - < 0.0015%

Other components (>20%):		
CAS: 1317-65-3 EINECS: 215-279-6 REACH: [1]	Limestone (Calcium carbonate) Consisting of: 471-34-1 Calcium carbonate (> 90%); 16389-88-1 Calcium/Magesium carbonate (0 - 10%); 14808-60-7 Quartz (SiO_2) (0 - 10%); 37244-96-5 Feldspar (0 - 5%); 12001-26-2 Mica - Potassium aluminum silicate (Muscovite) (0 - 5%)	50 - < 100%

Additional information:
For the wording of the listed hazard phrases refer to section 16.

Note 10 (EU 2020/217): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

[1] Not subject to registration in accordance with EC 1907/2006 Annex V (point 7) or Article 2.

SECTION 4: First aid measures

Description of first aid measures



First aid

General information:
For first responder no special personal protective equipment is required. First responder should avoid contact with the product.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 3)

After inhalation:
Take affected persons into fresh air and keep quiet. Seek medical treatment in case of complaints. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

After skin contact:
Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing. Wash contaminated clothes before reuse. Clean contamionated shoes before reuse. If skin irritation continues, consult a doctor.

After eye contact:
Do not rub eyes because additional damage to eyes can be caused by mechanical stress. If necessary, remove contact lenses and flush the eye immediately while holding eyelids open to water for at least 20 minutes. If possible, isotonic eyewash solution (e. g. 0,9% NaCl). Always consult an occupational physician or ophthalmologist.

After swallowing:
Do not induce vomiting. If conscious rinse mouth with water and drink plenty of water. Consult a physician or poison control center.

Most important symptoms and effects, both acute and delayed
Symptoms and effects are described in section 2 and 11.

Hazards:
No further relevant information available.

Indication of any immediate medical attention and special treatment needed
If a physician is to be consulted, as per possibillity he should be presented this safety data sheet.

SECTION 5: Firefighting measures

Extinguishing media
The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

Suitable extinguishing agents:
The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

Special hazards arising from the substance or mixture
This product is neither explosive nor flammable, and non-oxidizing with other materials. Particular danger of slipping on leaked/spilled product.

Advice for firefighters
No special measures required. Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures
If appropriate, reference must be made to exposure controls and personal protection (see section 8).

Environmental precautions
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Methods and material for containment and cleaning up
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 4)

Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

Precautions for safe handling:
Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Wear protective clothing. Washing facilities / Water for cleaning yes and skin should be available. Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product. Do not eat, drink, smoke or sniff while working.

Information about fire - and explosion protection:
No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:
Keep out of reach of children. Store in cool, dry place in tightly closed receptacles.

Information about storage in one common storage facility:
Keep away from foodstuffs, beverages and feed.

Further information about storage conditions:
Protect from frost. Protect from heat and direct sunlight.

Miniumum storage life:
Minimum storage life (+5°C up to 25°C): See indication on package.

Storage class: 12

Specific end use(s)
No further relevant information available.

SECTION 8: Exposure controls/personal protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)	
WEL (Great Britain)	Long-term value: 10* 4** mg/m³ *total inhalable **respirable

DNELs		
13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)		
Oral	Long term exposure	700 mg/kg bw/d (Consumer)
Inhalative	Systemic - Long term exposure	10 mg/m³ (Employee)
2682-20-4 2-Methyl-2H-isothiazol-3-one		
Oral	Long term exposure	0.027 mg/kg bw/d (Consumer)
	Short term exposure	0.053 mg/kg bw/d (Consumer)
Inhalative	Local - Long term exposure	0.021 mg/m³ (Consumer)
		0.021 mg/m³ (Employee)
	Local - Short term exposure	0.34 mg/m³ (Consumer)
		0.34 mg/m³ (Employee)

(Contd. on page 6)

(Contd. of page 5)

PNECs	
13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)	
Freshwater	0.127 mg/l
Marine water	1 mg/l
Soil	> 100 mg/kg
Sediments (Freshwater)	> 1,000 mg/kg
Sediments (Marine water)	100 mg/kg
Sewage plant	100 mg/l
2682-20-4 2-Methyl-2H-isothiazol-3-one	
Freshwater	0.00339 mg/l (not specified)
Soil	0.047 mg/kg (not specified)
Sediments (Marine water)	0.00339 mg/kg (not specified)
Sewage plant	0.23 mg/l (not specified)
26530-20-1 2-Octyl-2H-isothiazol-3-one	
Freshwater	0.0022 mg/l (not specified)
Marine water	0.00022 mg/l (not specified)
Soil	0.0082 mg/kg (not specified)
Sewage plant	0.0475 mg/l (not specified)

Ingredients with biological limit values:
Void

Additional information:
The lists valid during the making were used as basis.

Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately and thoroughly clean it before using it again. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Ensure that washing facilities are available at the work place.

Respiratory protection:



Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)

Hand protection:



Hand protection: Chemical resistant protective gloves according EN ISO 374

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Check protective gloves prior to each use for their proper condition. Preventive skin protection by use of skin-protecting agents is recommended. To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves:
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 6)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:
Polychloroprene (material thickness ≥ 0.5 mm ; breakthrough time ≥ 480 min.)
Nitrile rubber (material thickness ≥ 0.35 mm ; breakthrough time ≥ 480 min.)
Butyl rubber (material thickness ≥ 0.5 mm ; breakthrough time ≥ 480 min.)
Fluororubber (material thickness ≥ 0.4 mm ; breakthrough time ≥ 480 min.)
Synthetic rubber gloves
PVC gloves
Neoprene protective gloves with a material thickness of ≥ 0.5 mm are recommended.
Neoprene gloves

Not suitable are gloves made of the following materials:
Non-liquid-tight gloves made of fabric, leather or similar materials.

Eye/face protection:



In case of splash risk use tightly fitting safety goggles according to EN 166.

Body protection:



Protective work clothing

Risk management measures:
An operator training/guidance in the correct use of personal protective equipment is necessary to ensure the required level of effectiveness.

Information about design of technical facilities
No further data; see item 7.

Environmental exposure controls
Avoid release in the environment. Use the surplus or dispose it of properly.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

General Information	
Physical state	Fluid
Appearance:	
Form:	Pasty
Colour:	Different according to colouring
Odour:	Mild
Odour threshold:	Not safety relevant
pH at 20 °C (68 °F)	8 - 10
Change in condition	
Melting point/freezing point:	~ 0 °C (~ 32 °F) (ISO 3016)
Boiling point or initial boiling point and boiling range	100 °C (212 °F)
Flammability	Product is not flammable.

(Contd. on page 8)

(Contd. of page 7)

Flash point:	Not applicable
Auto-ignition temperature:	> 400 °C (> 752 °F) (DIN 51794)
Decomposition temperature:	> 825°C to CaO and CO_2
Oxidising properties:	None
Explosive properties:	Product does not present an explosion hazard.
Lower and upper explosion limit	
Lower:	Not determined
Upper:	Not determined
Ignition temperature:	Product is not selfigniting.
Vapour pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density and/or relative density	
Density at 20 °C (68 °F):	1.6 g/cm³ (13.35 lbs/gal)
Particle size	
Viscosity:	
Dynamic at 20 °C (68 °F):	> 5,000 mPas (DIN 53019)
Solubility	
Water:	Fully miscible
Solids content:	80 - 84 %
Solvent content:	
Organic solvents:	0.2 %
VOC without water (EC):	0.01 g/l
VOC with water (EC):	0 - < 0.01 g/l
VOC with water (EC):	0 %

Other information

Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

Reactivity
No dangerous reactions known.

Chemical stability:
The product is stable as long as it is stored properly and dry.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

KREISEL®

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 8)

Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.

Possibility of hazardous reactions
No dangerous reactions known.

Conditions to avoid
No further relevant information available.

Incompatible materials
No further relevant information available.

Hazardous decomposition products
No dangerous decomposition products known.

Miniumum storage life:
Minimum storage life (+5°C up to 25°C): See indication on package.

Additional information:
No further relevant information available.

SECTION 11: Toxicological information

Information on hazard classes as defined in Regulation (EC) No 1272/2008
The product was not investigated. The statement is derivated from the properties of the single components.

Acute toxicity:
Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
1317-65-3 Limestone (Calcium carbonate)		
Oral	LD_{50}	6,450 mg/kg (Rat) (RTECS Data)
13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)		
Oral	LD_{50}	> 5,000 mg/kg (Rat) (OECD 425)
	Carcinogenicity	(Mouse) (ECHA Registration dossier) no effects observed
Dermal	LD_{50}	> 5,000 mg/kg (Rabbit)
2682-20-4 2-Methyl-2H-isothiazol-3-one		
Oral	LD_{50}	232 - 249 mg/kg (Rat) (OECD 401)
Dermal	LD_{50}	242 mg/kg (Rat) (OECD 402)
Inhalative	LC_{50} (4h)	0.05 mg/l (ATE)
	LC_{50} (4h)	0.11 mg/l (Rat) (OECD 403)
26530-20-1 2-Octyl-2H-isothiazol-3-one		
Oral	LD_{50}	125 mg/kg (ATE)
		125 mg/kg (Rat) (OECD 401)
Dermal	LD_{50}	311 mg/kg (ATE)
		311 mg/kg (Rat) (OECD 402)
Inhalative	LC_{50} (4h)	0.5 mg/l (ATE)
64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one		
Oral	LD_{50}	567 mg/kg (ATE)
Inhalative	LC_{50} (4h)	0.05 mg/l (ATE)
	LC_{50} (4h)	0.055 - 0.53 mg/l (Rat)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

KREISEL®

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 9)

Other information (about experimental toxicology):		
13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)		
Oral	OECD 414 (Prenatal Developmental Toxicity)	(Rat) no effects observed
Irritation of skin	OECD 404 (skin)	(Rabbit) not corrosive
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritant
Sensitisation	OECD 429 (LLNA)	(Mouse) not sensitizing
	OECD 421 (Reproduction screening test)	(Rat) no effects observed
2682-20-4 2-Methyl-2H-isothiazol-3-one		
Oral	OECD 408 (Repeated dose oral toxicity 90d)	19 mg/kg bw/day (Rat)
Irritation of skin	OECD 404 (skin)	(Rabbit) corrosive
Sensitisation	OECD 406 (sensitization)	(Guinea pig) sensitizing
26530-20-1 2-Octyl-2H-isothiazol-3-one		
Oral	OECD 471 (In vitro - Mutation, Ames-Test)	(Salmonella typhimurium) Negative
Irritation of skin	OECD 404 (skin)	(Rabbit) Corrosive Category 1B
Irritation of eyes	OECD 405 (eye)	(Rabbit) Irreversible effects Category 1
Sensitisation	OECD 406 (sensitization)	(Guinea pig) Sensitizing Category 1

On the skin:
Based on available data, the classification criteria are not met.

On the eye:
Based on available data, the classification criteria are not met.

Sensitization:
Sensitising effect by skin contact is possible by prolonged exposure.
Based on available data, the classification criteria are not met.

Germ cell mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity:
Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure (STOT SE):
Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure (STOT RE):
Based on available data, the classification criteria are not met.

Aspiration hazard:
Based on available data, the classification criteria are not met.

Practical experience
No further relevant information available.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

KREISEL

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 10)

General comments
No further relevant information available.
Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

*

SECTION 12: Ecological information

Toxicity
The product was not investigated. The statement is derivated from the properties of the single components.

Aquatic toxicity:	
1317-65-3 Limestone (Calcium carbonate)	
LC_{50} (96h)	> 100 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)
LC_{50} (48h)	> 100 mg/l (Water flea - daphnia magma) (OECD 202)
EC_{50}	> 14 mg/l (Algae - desmodesmus subspicatus) (OECD 201)
	> 1,000 mg/l (Activated sewage sludge) (OECD 209)
13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)	
LC_{50} (48h)	5.5 mg/l (Water flea - daphnia magma)
LC_{50} (96h Marine water)	> 10,000 mg/l (Fish)
LC_{50} (96h Freshwater) (static)	> 100 mg/l (Goldfish) (OECD 203)
EC_{50} (48h)	> 1,000 mg/l (Water flea - daphnia magma) (ASTM Standard E729)
EC_{50} (72h)	5.83 mg/l (Algae - pseudokirchneriella subcapitata)
EC_{50} (3h)	> 1,000 mg/l (Activated sludge organisms) (OECD 209)
EC_{50} (7d)	> 100 mg/l (Lemna minor) (OECD 221)
NOEC (48h)	1 mg/l (Water flea - daphnia magma)
NOEC (21d)	> 10 mg/kg (Water flea - daphnia magma) (OECD 202)
NOEC (28d) (static)	> 100 mg/l (Chironomus riparius) (OECD 219) Soil
NOEC (32d)	> 1 mg/l (Scenedesmus quadricauda)
NOEC (8d)	> 1,000 mg/l (Zebrafish - danio rerio) (OECD 212)
2682-20-4 2-Methyl-2H-isothiazol-3-one	
LC_{50} (96h Marine water)	2.98 mg/l (Water flea - daphnia magma)
LC_{50} (96h Freshwater)	0.934 mg/l (Water flea - daphnia magma)
LC_{50}	4.77 mg/l (Fish) (OECD 203)
EC_{10}	0.044 mg/l (Water flea - daphnia magma) (OECD 211)
	4.93 mg/l (Fish)
EC_{50}	41 mg/l (Activated sewage sludge) (OECD 209)
	0.103 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
EC_{50} (16h)	2.3 mg/l (Pseudomonas putida)
26530-20-1 2-Octyl-2H-isothiazol-3-one	
LC_{50} (96h)	0.03 mg/l (Rainbow trout - oncorhynchus mykis)
LC_{50} (96h Freshwater)	0.122 mg/l (Fish - pisces)
EC_{10}	0.068 mg/l (Algae)
	0.022 mg/l (Fish - pisces)
	0.035 mg/l (Invertebrate)
EC_{50}	30.4 mg/l (Activated sewage sludge)

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 11)

EC_{50} (48h)	0.32 mg/l (Water flea - daphnia magma)
	0.42 mg/l (Water flea - daphnia) (OECD 202)
EC_{50} (72h)	0.084 mg/l (Algae scenedesmus subcapitatus) (OECD 201) S 63
EC_{50} (96h)	0.047 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)
EC_{50}/LC_{50}	0.15 mg/l (Algae)
	0.181 mg/l (Invertebrate)
IC_{50} (72h)	0.084 mg/l (Algae scenedesmus subcapitatus) (OECD 201)
64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one	
LC_{50} (96h)	0.014 mg/l (Perch - lepomis macrochirus) (OECD 203)
	0.0027 mg/l (Rainbow trout - oncorhynchus mykis)
EC_{50}	5.7 mg/l (Activated sludge organisms)
ErC_{50} (72h)	0.077 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
EC_{50} (48h)	0.0057 mg/l (Water flea - daphnia magma)
EC_{50} (72h)	0.048 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
NOEC (96h)	0.00056 mg/l (Rainbow trout - oncorhynchus mykis)

Persistence and degradability
A part of the components is biodegradable.

26530-20-1 2-Octyl-2H-isothiazol-3-one		
Oral	OECD 309 Simulation Biodegradation - Surface Water	0.6 - 1.4 d (not specified) S 635

Bioaccumulative potential	
26530-20-1 2-Octyl-2H-isothiazol-3-one	
OECD 107 LogKow (Shake Flask Method)	2.92 (n-Octanol/Water)

Mobility in soil
No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.

Other adverse effects
No further relevant information available.

Literature
No further relevant information available.

Ecotoxical effects:
No further relevant information available.

Behaviour in sewage processing plants:	
2682-20-4 2-Methyl-2H-isothiazol-3-one	
EC_{20} (3h)	2.8 mg/l (Activated sludge organisms) (DIN 38412-3 TTC-Test)
26530-20-1 2-Octyl-2H-isothiazol-3-one	
EC_{20} (0,5h)	10.4 mg/l (Activated sewage sludge) (TTC-Test 8901 Macherey Nagel)
EC_{20} (3h)	7.3 mg/l (Activated sewage sludge) (OECD 209)

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

KREISEL

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 12)

OECD 303 A Activated Sludge Units	> 83 % (Activated sewage sludge) S 313


Additional ecological information:

General notes:
Not hazardous for water.

SECTION 13: Disposal considerations

Waste treatment methods

Recommendation:



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of contents/container in accordance with local/regional/national/international regulations.

17 09 04 for the setted product
08 01 20 for residues of the unprocessed product
15 01 02 for the completely emptied packaging

Uncleaned packaging

Recommendation:
Disposal must be made according to official regulations.
Recycle only completely emptied packaging.

Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

UN number or ID number **ADR, ADN, IMDG, IATA**	Void
UN proper shipping name **ADR, ADN, IMDG, IATA**	Void
Transport hazard class(es) **ADR, ADN, IMDG, IATA** **Class**	Void
Packing group **ADR, IMDG, IATA**	Void
Environmental hazards **Marine pollutant:**	No
Special precautions for user	Not applicable
Maritime transport in bulk according to IMO instruments	Not applicable
UN "Model Regulation":	Void

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 13)

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Directive (EU) 2012/18
Named dangerous substances - ANNEX I :
None of the ingredients is listed.

Biozide ingredients (98/8/EG):
Data based on recipe and information on the raw materials from the supply chain.

Tetramethylolacetylene diurea	< 0.03%
1,2-Benzisothiazol-3(2H)-one	< 0.005%
2-Bromo-2-nitropropane-1,3-diol	< 0.0025%
2-tert-Butylamino-4-ethylamino-6-methylthio-s-triazine (Terbutryn)	≥ 0.00025 - < 0.0025%
3-Iodo-2-propynylbutylcarbamate	< 0.0015%
2-Methyl-2H-isothiazol-3-one	< 0.0015%
2-Octyl-2H-isothiazol-3-one	≥ 0.00025 - < 0.0015%
4,5-dichloro-2-octyl-2H-isothiazol-3-one	≥ 0.00025 - < 0.0015%

Classification according 2004/42/EG:
IIA(c) 40 - this product contains < 40 g/l VOC (see chapter 9)

Chemical safety assessment
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Reasons for changes:
* Data compared to the previous version altered.

Relevant phrases:
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH071 Corrosive to the respiratory tract.

Advice for instructions:
Additional trainings, which go beyond the prescribed training in activities involving hazardous substances are not required.

Literature and the data sources:

Department issuing MSDS:
Product safety department (+43/(0)5522-41646-0 / klaus.ritter@fixit-gruppe.com)

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2023 Version number: RO/ 3 Revision: 26.05.2023

MAX PROTECT 042

(Contd. of page 14)

Contact:
Dr. Klaus Ritter

Date of previous version: 14.02.2023

Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
MAK: Maximale Arbeitsplatz-Konzentration (maximum concentration of a chemical substance in the workplace, Austria/ Germany)
PBT: persistent, bioaccumulative and toxic properties
vPvB: very persistent, bioaccumulatice properties
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1: Skin corrosion/irritation – Category 1
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Further information:
The information in this safety data sheet describe the safety requirements of our product and is based on our current state of our knowledge. They provide no assurance of product quality. Existing laws, ordinances and regulations, including those that are not mentioned in this data sheet must be observed by the recipient of our products in their own responsibility.