




Fixit 777


Final render extra white


Areas of use: Fixit 777 is a mineral finish coat for cement, lime and gypsum-based substrates for outdoor and indoor use. The surface must be clean, dry and stable. The prior application of Fixit 475 Primer for mineral plasters is recommended.

- Properties:**
- Mineral-based and biocide-free
 - Extra white
 - Diverse structures possible
 - Weather resistant
 - On gypsum, limestone and cement substrates
 - Range of grain sizes
 - ECO certified

Application procedure:



Technical data					
Packaging type					
Unit per pallet	40 bags/pal.				
Quantity per unit	25 kg/bag				
Granulation	1 mm	1.5 mm	2 mm	3 mm	4 mm
dashed	Full abrasion				
Consumption	approx. 2 kg/m ²	2,2 - 2,5 kg/m ²	2,9 - 3,3 kg/m ²	3,9 - 4,2 kg/m ²	5 - 5,3 kg/m ²
Application time	approx. 90 min				

Packaging type					
Unit per pallet	40 bags/pal.				
Quantity per unit	25 kg/bag				
Granulation	4 - 6 mm	1.5 mm	2 mm	3 mm	0.5 mm
dashed	Full abrasion	Negative	Negative	Negative	Slurry plaster
Consumption	5,2 - 5,5 kg/m ²	approx. 2,1 kg/m ²	2,6 - 3 kg/m ²	approx. 3,5 kg/m ²	1,5 - 2 kg/m ²
Application time	approx. 90 min				

- Composition:**
- Binder: White lime, white cement
 - Aggregates: Marble sand
 - Additives: Water retention agents, air entraining agents, bonding agents, water repellent medium

Basics: The general rules of building construction must be observed, in addition to the current notes published by the «Swiss Association of Painters and Plasterers SMGV», the recommendations SIA 242 «Rendering and Plastering» and the information in this technical data sheet.

Application procedure: Fixit 775 is mixed with clean water. On substrates which absorb water poorly, adhesion must be improved by adding to the mixing water approximately 1 L of Fixit 497 Plaster and Mortar Emulsion per sack .

Post-application treatment: The freshly applied render should be protected from exposure to bad weather and direct sunshine. Provide shade, additional humidification, protection from driving rain and hail etc. as necessary.



Fixit 777

Final render extra white

Storage: Store in a dry place on wooden battens. Storage life min. 12 months. Binding properties may be affected if stored for longer.

Certificates:



Important note: Do not use if air or ground temperature is below + 5 ° C.
When negative texture is being worked with a mineral finish coat using a plastic finishing trowel, then the trowel **MUST** be carefully selected in order to achieve the necessary structure.

Drying
The setting time of Fixit 777 depends on the temperature and relative humidity of the surroundings. Low temperatures and/or high humidity delay the drying process. After about 10 days at + 20° C air and substrate temperature, and 65 % relative humidity, painting may begin. Basically, the Fixit 777 may only be painted after sufficient time has elapsed to allow complete carbonation to occur.