



FLEXIBLE FACADE BOARD

insulation panel

Areas of application: Characterized by faster binding, compared to standard flooring base
Reinforced with a reinforcing mesh
After painting with the ACRYLIC AZURE1003, it is possible to achieve different colour variants.

- Properties:**
- High elasticity
 - Natural wood pattern
 - Elastic
 - Waterproof
 - Frost-proof

Application procedure:



Technical data	
Item no.	34877
Quantity per unit	10 pcs./carton
Length	1,980 mm
Width	160 mm
Thickness	3 mm
Consumption	3.16 Stk./m ²

- Material base:**
- Polymers
 - Fillers
 - Mesh of glass fibre

Surface: Substrates should be free from dust, soot, grease, lubricants, anti-adhesive agents, paints, excess mortar etc. Symptoms of biological aggression (fungi, mildew) should be removed using SEPTOBUD 1008 preparation. Old, destroyed coatings with low strength must be removed. Prime weak beds with GRUNTOLIT-SG 302

Types of substrate: **Reinforcing layer in the thermal insulation system:** without additional priming
Concrete: Prime with GRUNTOBET 310
Cement-lime plaster: Prime with GRUNTOLIT-W 301 or EXPERT 6
Old plasters: Prime with GRUNTOLIT-SG 302 or EXPERT 5

Application procedure: In the case of thermal insulation system, the plank must be fixed directly to styrofoam or well-set reinforced layer (min. after 3 days) or to another stable bed e.g. plaster. Fix by means of the DISPERSION ADHESIVE 111. With regard to this adhesive, it is necessary to observe the minimum drying temperature which is +10 °C. It is possible to fix by means of a cement, white adhesive, etc.: EXPERT 2 WHITE, GEL ADHESIVE 110B. After min. 48 from fixing, the plank must be covered carefully with facade paint if necessary (e.g. ACRYLIC PAINT 001). 24 hours from painting, it must be carefully covered with Acrylic azure 1003 in a chosen colour along the grains using a brush. To achieve the rustic effect, directly after application, the scumble shall be wiped delicately with a clean, dry sponge. It is possible to apply the scumble twice, depending on the required effect
While working on corners, DISPERSION ADHESIVE 111 must be used to finish the plank edges

Application conditions: While fixing and painting, apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product.

General information: This data sheet invalidates all previous editions. The content of this safety sheet represents our current knowledge and practical experience. It is only general information and does not result in any liability on the part of the manufacturer for the design and method of use. There may be differences and specific conditions of execution. The product is to be used in accordance with the required technical knowledge and in accordance with the occupational safety rules.